



SPECIAL CHARACTERISTICS

- Suitable for raised face flanges
- Lightweight
- Compact
- Economical
- Easily installed
- Anti-slam
- Face to face to BS 7438 and EN 558.2
- Suitable for vertical pipe

Model	7432	7431	7437
Body	P.F.A. lined	P.F.A. lined	P.F.A. lined
Seat Carrier	P.F.A. lined	P.F.A. lined	P.F.A. lined
Disc	P.T.F.E.	Ceramic	Hastelloy
Spring	Titanium	Suffix 'T'	
	Hastelloy	Suffix 'H'	
	P.F.A. coated	Suffix 'C'	

Principle Dimensions

Nominal size 'DN' (mm)	15	20	25	40	50	65	80	100
Outlet bore 'DI' (mm)	19	24	30	46	56	72	81	100
Length 'L' (mm)	25	32	36	45	56	63	71	80
Outside diameter 'DO' (mm)	See table on page 3							
Weight (Kg)	0.2	0.4	0.8	1.0	2.0	3.0	5.0	7.0

Working temperatures up to 200°C
 Working pressures up to 50 Bar
 Special springs on request

Abacus Wafer Check Valves

t: +44 (0)1505 681777
 f: +44 (0)1505 683999

www.abacusvalves.com
 sales@abacusvalves.com

Block 4 Lochshore East
 Industrial Estate Glengarnoch
 Ayrshire KA14 3DB

NOTES

- Wafer pattern design offers significant space and weight reduction compared with traditional flanged valve design
- Superior by design
- 24 hour quotation turn around
- Comprehensive stocks
- Worldwide distribution
- Technical assistance and advice always available